

# PosiTest® DFT

## Coating Thickness Gage

### *Ideal for...*

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers

### *2 Models...*

**Ferrous** for STEEL

**Combo** for ALL METALS



simply  
measures

**DeFelsko®**  
The Measure of Quality

# PosiTest<sup>®</sup> DFT

## Coating Thickness Gage

### Two Models

- **PosiTest DFT Ferrous**  
measures non-magnetic coatings on steel.
- **PosiTest DFT Combo**  
measures both non-magnetic coatings on steel AND non-conductive coatings on aluminum, brass, etc. **Automatically** recognizes the substrate and takes a measurement.



### Features

- Fast, repeatable measurements
- No calibration required for most applications
- ZERO feature for rough or curved surfaces
- Handy RESET feature when no zero reference is available
- Strong, wear-resistant, ruby-tipped probe
- Unique FLIP Display enables right-side-up viewing in any position
- Audible and visible measurement indication
- V-groove in probe for positioning on cylindrical parts
- Mila/Microns switchable
- Basic instructions on the back of each gage
- Built-in wrist strap for added convenience and safety
- 2 Year Warranty

### Specifications

Measurement Range	0 – 40 mils	0 – 1000 $\mu$ m
Accuracy	$\pm(0.1 \text{ mils} + 3\%)$	$\pm(2\mu\text{m} + 3\%)$
Size	4 x 1.5 x 0.9 in.	100x38x23 mm
Weight	2.5 oz.	70 g



**Unique FLIP Display**  
enables right-side-up  
viewing in any position



**Gage Comes Complete** with built-in probe, wrist strap, plastic shims, hard shell storage case, AAA battery, instructions and two (2) year warranty.

Conforms to: ISO 2178/2360/2808,  
pREN ISO 19840, ASTM B244/B499/B659/D1186/D1400/D7091/E376/G12,  
BS3900-C5, SSPC-PA2 and others. Certificate of Calibration traceable to NIST available.