

2501-I Remote Airborne Particle Counter

0.1 CFM (2.83 LPM)



The Particles Plus 2501-1 Remote Particle Counter measures 0.5 μ m and 5.0 μ m with a flow rate of 0.1 CFM (2.83 LPM). Integration is easy into a real-time monitoring or building management system via Modbus RTU or ASCII. The 2501-1 models are the smallest remote particle counters in the market and have easy mounting options. The Particles Plus 2501-1 units comply with ISO 21501-4 and include a 2 year limited warranty.

Features and Benefits

- 2501-1 Measures 0.5 μm and 5 μm
- 0.1 CFM (2.83 LPM) flow rate with onboard pressure loss alarm
- Long life laser diode technology
- World's smallest 0.1 CFM remote particle counter
- · Measures 2 channels of simultaneous data.
- MODBUS™ RTU or ASCII Outputs
- Connect using RS485
- Concentration limit of 500,000 per ft³
- LED Status Indication
- Complies with ISO 21501-4 and JIS B9921 standards
- · Seamless integration into a facility monitoring system
- · Light weight stainless steel enclosure
- · 2 year warranty. Extended warranties available

Specifications

Model	2501-1
Channel Sizes	0.5 μm and 5.0 μm
Counting Efficiency	50% at 0.5 μm; 100% for particles > 0.75 μm (per JIS)
Concentration Limits	500,000 particles / ft3 at 5% coincidence loss
Light Source	Long life laser diode
Zero Count Level	<1 count / 5 minutes (per JIS B9921)
Flow Rate	0.1 CFM (2.83 LPM)
Flow Control	Critical orifice
Vacuum Requirements	External vacuum >15" (38.1 cm) of Hg
Calibration	NIST Traceable
Sample Probe/Tubing	Isokinetic sampling probe
Communication Interface	Modbus™ RTU or ASCII outputs (specified upon order)
Power	9-30VDC
Dimensions $(L \times W \times H)$	$1.8" \times 3.7" \times 1.5"$ (4.5 cm x 9.3 cm x 3.8 cm)
	does not include probe
Weight	0.62 lb (0.28 kg)
Standards	ISO 21501-4 and JIS B9921
Warranty	2 year limited warranty
Operating Conditions	5° to 35°C 20% to 95%RH non-condensing
Storage Conditions	-20° to 50°C Up to 98%RH non-condensing
Optional Accessories	Isokinetic sampling probe, purge filter, vacuum and sample tubing





