



POWER SUPPLIES

(1496 S62)	Id-No. 00.14966.200000
Features:	very large input range, distribution function and suitability for outdoor installation
Input:	100...240 VAC switching
Output:	24 V · max. 6.3 A · 150 W
Housing:	polycarbonate • RAL 7035 (light-grey) • 278 x 278 x 130 mm • IP 65 • Cable glands 5x M16 x 1.5/ 1x M20 x 1.5/ 1x M25 x 1.5
Weight:	approx. 2.6 kg
Mast mounting:	Id-No. 32.14622.220000 (optional)



(1496 S63)	Id-No. 00.14966.300 000
	same as (1496 S62) but 24 VDC • 2.5 A • 48 W
Dimensions:	278 x 188 x 130 mm
Weight:	approx. 2.4 kg
Mast mounting:	Id-No. 32.14622.220000 (optional)



power[cube]	
Features:	compact cube, very robust, all-weather suitable for outdoor installation
Housing:	UV- and weather resistant • approx. 190 x 190 x 190 mm
Mast mounting:	Id.-No. 32.14966.030000 (optional)

VERSIONS

power[cube]	Id-No. 00.14966.715000
Input:	90...264 VAC
Output:	24 V · max. 6.5 A
Weight:	approx. 1,8 kg

power[cube]	Id-No. 00.14966.724000
Input:	90...264 VAC
Output:	24 V · max. 10.0 A
Weight:	approx. 2.5 kg

power[cube]	Id-No. 00.14966.748000
Input:	90...264 VAC
Output:	24 V · max. 20.0 A
Weight:	approx. 2.5 kg

